



Outdoor P3.9-7.8 / P7.8-7.8
1000X500mm (WxH)



HoFly Transparent Outdoor LED Display

Outdoor Concert / Music Festival

HoFly series Specification

Pixel Pitch	P3.9-7.8 outdoor	P7.8-7.8 outdoor
LED per pixel	SMD1921	SMD1921
Pixel Density(per sqm)	32768	16384
Module Dimension(WxH)	500x125mm	500x125mm
Module Resolution	128x16 pixels	64x16 pixels
Scan Rate	1/8	1/4
Cabinet Dimension(WxH)	1000x500mm	1000x500mm
Cabinet Resolution	256x64 pixels	128x64 pixels
Light transmittance	≥70%	≥70%
Best View Distancing	≥3m	≥7m
Refresh Rate	3840Hz	3840Hz
Viewing Angle(H/V)	160°/140°	160°/140°
Cabinet Material	Die-casting aluminium	Die-casting aluminium
Maintenance	Rear	Rear
Single Cabinet Weight	7.5kgs	7.5kgs
Brightness	4000-4500nits	3500-4000nits
Max Power Consumption	600w	600w
Avg Power Consumption	300w	300w
Ingress Protection	IP65(F) / IP54(R)	IP65(F) / IP54(R)
Lifetime(Hrs)	100,000	100,000

*product spec are for reference only,the final interpretation right of product is reserved by HoliLED



1. website



2. facebook



3. skok



4. youtube

SHENZHEN HOLILED TECHNOLOGY CO.,LTD

Add:5F,Building A,ShengDe Lan Industrial Park,
Kukeng,Guanlan,Shenzhen,China

<http://www.holiled.com>

sales@holiled.com
sales01@holiled.com
sales02@holiled.com
sales03@holiled.com
sales04@holiled.com
sales05@holiled.com
sales06@holiled.com
sales07@holiled.com
sales08@holiled.com